



HINO 700 PROFIA SS1E TH

Mechanical

Performa

Kecepatan Maksimum 119(KM/H)

Daya Tanjak (tan Ø) 51.3

Model Mesin

Model e13c vt

Model Tipe Diesel 4 Stroke, In Line (Common Rail)

Tenaga Maksimum (PS/rpm) 480 / 1800

Torsi Maksimum (Kgm/rpm) 220 / 1100

Jumlah Silinder 6

Diameter x Langkah Piston (mm) 137 x 146

Isi Silinder (cc) 12 ,913

Kopling

Tipe Dry Twin plate with Damper Spring

Diameter Cakram 387

Transmisi

Tipe eaton rtl016918b 18 speed

Perbandingan Gigi 4.555

C -

ke-1 14,402 / 12,287

ke-2 8,561 / 7 ,303

ke-3 6,048 , 5,160

ke-4 4.384 / 3.740

ke-5 3.201 / 2.731

ke-6 2 288 1 ,952

ke-7 1,617 / 1 ,379

ke-8 1.172 / 1 .000

Mundur	low 15.057 / 12.485
--------	---------------------

Kemudi

Tipe	Integral Power Steering Recirculating with Hydraulic Booster
------	--

Minimal Radius Putar	7.5 m
----------------------	-------

Sumbu

Belakang	Full Floating Type Hypoid Gear
----------	--------------------------------

Depan	Reversed Elliot, I Section
-------	----------------------------

Perbandingan Gigi Akhir	4 ,555
-------------------------	--------

Sistem Penggerak	6 x 4
------------------	-------

Rem

Rem Utama	Full Air Brake with Dual Circuit (Include ABS)
-----------	--

Rem Pelambat	Engine Retarder
--------------	-----------------

Rem Parkir	Wheel Parking
------------	---------------

Roda & Ban

Ukuran Rim	22, 5 x 7 50v 165
------------	-------------------

Ukuran Ban	11r-22,5
------------	----------

Jumlah Ban	10 (+1)
------------	---------

Suspensi

Depan & Belakang	Semi elliptical; Leaf Spring with Shock Absorber & Stabilizer Semi-elliptical; Leaf Spring with Shock Absorber
------------------	--

Sistim Listrik Accu

Accu	12v 120ah x 2
------	---------------

